ORDER FOR SUPPLIES OR SERVICES						PAGE 1 OF 24							
	ACT PURCH O		ER/AGREEMENT NO.	2. DELIV	VERY ORDER	/CALL NO.	3. DATE OF ORD (YYYYMMMDD) 2004JUN18	ER/CAL		JISITION/PURCH RE	QUEST NO.	5. PRIORITY DOA4	
6. ISSUED	BY			CODE	W56HZV	7. ADMINIST	ERED BY (If other t	han 6)	SEE S		1501A	8. DELIVERY FOB	
AMS MAR WAR	REN, MICHI	RY GAI	BLDG 231 (586)574-6359 N 48397-5000 @TACOM.ARMY.MIL ING.TACOM.ARMY.M	1IL		EMM 889	A INDIANAPOLETT J. BEAN C 9 E. 56TH ST. IANAPOLIS, IN	ENTER 462		ADP PT: HO033	27	X DESTINATION OTHER (See Schedule if other)	
9. CONTR	ACTOR			CODE	0JT27	FACIL		10. DE		OB POINT BY (Date)		11. X IF BUSINESS IS	
	•						•	(Y	YYYMMMDI	<b>D</b> )		X SMALL	
	HUPP I BOX 15		USTRIES 9						SCHEDULE			SMALL	
NAME AND ADDRESS		IAYI	NE, IN. 46885-50	)09					SCOUNT TEI 30 Days	RMS		DISADVANTAGED WOMAN-OWNED	
	•						•	13. M	AIL INVOICE	S TO THE ADDRESS	IN BLOCK		
14. SHIP T		BUS:	INESS: Other Sma	all Busi	1		U.S. T WILL BE MADE I		Block 15	COD	<b>р</b> Е НQ0337	MARK ALL	
	SCHEDULE			CODE		DFA DFA P.O	S - COLUMBUS S-CO/NORTH EN . BOX 182266 UMBUS OH 4	CENTE	MENT OPER		н <u>е</u> н <u>о</u> 0337	PACKAGES AND PAPERS WITH IDENTIFICATION NUMBERS IN BLOCKS 1 AND 2	
16. TYPE	DELIVERY/ CALL		THIS DELIVERY ORDER	R IS ISSUED	ON ANOTHER (	GOVERNMENT AG	GENCY OR IN ACCORD	ANCE W	ITH AND SUBJE	ECT TO TERMS AND COM	NDITIONS OF ABOV	E NUMBERED CONTRACT.	
OF ORDER	PURCHASE	x	Reference your	Oral		-	6HZV04Q1033	, D	ated	·			
												MAY PREVIOUSLY HAVE ME.	
	NAME OF CONTRACTOR SIGNATURE TYPED NAME AND TITLE DATE SIGNED (YYYYMMMDD)  If this box is marked, supplier must sign Acceptance and return the following number of copies:  17. ACCOUNTING AND APPROPRIATION DATA/LOCAL USE												
SEE	SCHEDULE												
18. ITEM		СНЕ	EDULE OF SUPPLIES/SE	ERVICE			20. QUANTITY ORDERED/ ACCEPTED*	7	21. UNIT	22. UNIT PRICE	23. AMOUNT		
	CONT F: KINI	rra irm	CHEDULE  CT TYPE: 1-Fixed-Price  OF CONTRACT: bly Contracts and	d Price	d Orders								
* If quantity	accepted by the	Go	vernment is 2	4. UNITED	STATES OF A	AMERICA					25. TOTAL	\$33,004.80	
same as qu If differen	uantity ordered,	indi ıant	cate by X. ity accepted below	BY:		GAPINSKI M@TACOM.ARM	/SIGNED/ Y.MIL (586)57			RDERING OFFICER	26. DIFFERENCES	3	
			N 20 HAS BEEN	1.				COIT	IRICIE II I G	ADEMINO OTTICER	I.		
	PECTED TURE OF AUTI	_	RECEIVED A RIZED GOVERNMENT I			ORMS TO CONT	c. DATE (YYYYMMMD)		d. PRINTE	D NAME AND TITLE SENTATIVE	OF AUTHORIZE	D GOVERNMENT	
e. MAILI	NG ADDRESS (	OF A	AUTHORIZED GOVERN	MENT RE	PRESENTATI	VE	28. SHIP. NO.		29. D.O. VOU	CHER NO.	30. INITIALS		
									32. PAID BY			TERIFIED CORRECT FOR	
f. TELEPHONE NUMBER g. E-MAIL ADDRESS					PARTIA FINAL	L	32.1 AID B1		33. AMOUNT	ERIFIED CORRECT FOR			
36. I CERTIFY THIS ACCOUNT IS CORRECT AND PROPER FOR PAYMENT.				31. PAYMENT				34. CHECK NU	MBER				
a. DATE			b. SIGNATURE AND	TITLE OF	CERTIFYING	OFFICER	COMPL				35. BILL OF L	ADING NO.	
(YYYYM!	MMDD)						PARTIA FINAL	L					
37. RECE	IVED AT		38. RECEIVED BY (P	'rint)	39. DATE RE		40. TOTAL CO TAINERS	N-	41. S/R ACCO	OUNT NUMBER	42. S/R VOUCE	IER NO.	

# Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 2 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

SUPPLEMENTAL	TATEODMATETON
SUPPLEMENTAL	INFURMATION

1

Regulatory Cite	Title	Date
52.204-4016	TACOM-WARREN ELECTRONIC CONTRACTING	JUL/2003
(TACOM)		

- (a) TACOM is now operating in an electronic contracting environment. All TACOM solicitations and awards are now distributed on the TACOM Warren Business Opportunities web page (<a href="http://contracting.tacom.army.mil/opportunity.htm">http://contracting.tacom.army.mil/opportunity.htm</a>) and are no longer available in hard copy. The TDPs and other documents, when available electronically, will be an attachment or linked to the solicitation package on the web. Please see submission guidelines at <a href="http://contracting.tacom.army.mil/userguide.htm">http://contracting.tacom.army.mil/ebidnotice.htm</a> for more information. Any requirements included in the solicitation take precedence over guidance found on the TACOM contracting web page.
- (b) You may need to use special software to view documents that we post on the home page. This viewing software is freeware, available for download at no cost from commercial web sites like Microsoft and Adobe. In cases where such software is required, we provide a link from our page to the commercial site where the software is available. Once you arrive at the software developer's site, follow their instructions to download the free viewer. You then can return to the TACOM home page.
- (c) You are required to submit your offer, bid, or quote electronically. See the provision entitled "Electronic Offers (or 'Quotes' or 'Bids') Required in Response to This Solicitation (or 'Request for Quotations')" for more specific information.
- (d) Any award issued as a result of this solicitation will be distributed electronically. Awards posted on the TACOM Warren Business Opportunities web page represent complete OFFICIAL copies of contract awards and will include the awarded unit price. This is the notice required by Executive Order 12600 (June 23, 1987) of our intention to release unit prices in response to any request under the Freedom of Information Act (FOIA), 5 USC 552. Unit price is defined as the contract price per unit or item purchased as it appears in Section B of the contract and is NOT referring to nor does it include Cost or Pricing data/information. If you object to such release, and you intend on submitting an offer, notify the PCO in writing prior to the closing date identified in this solicitation and include the rationale for your objection consistent with the provisions of FOIA. A release determination will be made based on rationale given.
- (e) If you have questions or need help in using the Acquisition Center Home Page, call our Electronic Contracting Help Desk at (586) 574-7059, or send an email message to: <a href="mailto:acqcenweb@tacom.army.mil">acqcenweb@tacom.army.mil</a>
- (f) If you have questions about the content of any specific item posted on our home page, please call the buyer or point of contact listed for the item. Additional help is available to small businesses from Government-funded Electronic Commerce Regional Centers (ECRCs) to implement EDI. Information on ECRC is available at <a href="http://www.ecrc.ctc.com">http://www.ecrc.ctc.com</a>

[End of Clause]

TDP IS COMPETITIVE

\*\*\* END OF NARRATIVE A 001 \*\*\*

# Reference No. of Document Being Continued PIIN/SIIN $^{W56HZV-04-P-1052}$ MOD/AMD

**Page** 3 **of** 24

Name of Offeror or Contractor: HUPP INDUSTRIES

ITEM NO	SUPPLIES/SERVICES	QUANTITY	UNIT	UNIT PRICE	AMOUNT
	SUPPLIES OR SERVICES AND PRICES/COSTS				
0001	NSN: 5340-01-380-8283 FSCM: 19207 PART NR: 57K0234 SECURITY CLASS: Unclassified				
0001AA	PRODUCTION QUANTITY	432	KT	\$76.40000	\$33,004.80
	NOUN: HARDWARE KIT, MECHAN PRON: EH4Y1676EH PRON AMD: 01 ACRN: AA AMS CD: 070011				
	Packaging and Marking  PACKAGING/PACKING/SPECIFICATIONS:  SEE PACKAGING REQ. SHEET  LEVEL PRESERVATION: Military  LEVEL PACKING: B				
	Inspection and Acceptance INSPECTION: Origin ACCEPTANCE: Origin				
	Deliveries or Performance  DOC SUPPL  REL CD MILSTRIP ADDR SIG CD MARK FOR TP CD  001 W56HZV4085T904 W45G19 M 2  DEL REL CD QUANTITY DAYS AFTER AWARD  001 432 0120				
	FOB POINT: Destination				
	SHIP TO: FREIGHT ADDRESS  (W45G19) XR W390 RED RIVER MUNITIONS CTR  HIGHWAY 82 WEST CL V TPF  GATE 44 BLDG 184  TEXARKANA TX 75507-5000				
	CONTRACT/DELIVERY ORDER NUMBER W56HZV-04-P-1052/0000				
0002	SECURITY CLASS: Unclassified				
0002AA	UNEXERCISED OPTION CLIN	432	KT	\$ 76.40000	\$33,004.80
	OPTION QUANTITY, PURSUANT TO SECTION I CLAUSE				

# Reference No. of Document Being Continued PIIN/SIIN $^{W56HZV-04-P-1052}$ MOD/AMD

Page 4 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

ITEM NO	SUPPLIES/SERVICES	QUANTITY	UNIT	UNIT PRICE	AMOUNT
	ENTITLED OPTION FOR INCREASED QUANTITY				
	SEPARATELY PRICED LINE ITEM				
	The quantity stated for the option CLIN DOES				
	NOT Form a part of the basic contractual				
	quantity. Part or all of it may, however, be added to the contract by exercise of the				
	option clause, at the discretion of the				
	Government.				
	(End of narrative B001)				
	Packaging and Marking				
	PACKAGING/PACKING/SPECIFICATIONS:				
	SEE PACKAGING REQ. SHEET				
	LEVEL PRESERVATION: Military				
	LEVEL PACKING: B				
	Inspection and Acceptance				
	INSPECTION: Origin ACCEPTANCE: Origin				
	Deliveries or Performance				
	DOC SUPPL				
	REL CD MILSTRIP ADDR SIG CD MARK FOR TP CD 001				
	DEL REL CD QUANTITY DEL DATE				
	001 432 UNDEFINITIZED				
	FOB POINT: Destination				
	SHIP TO: PARCEL POST ADDRESS				
	(Y00000) SHIPPING INSTRUCTIONS FOR CONSIGNEE (SHIP-TO) WILL BE FURNISHED PRIOR				
	TO THE SCHEDULED DELIVERY DATE FOR				
	ITEMS REQUIRED UNDER THIS				
	REQUISITION.				
	CONTRACT/DELIVERY ORDER NUMBER				
	W56HZV-04-P-1052/0000				
	1				

	CONTINUATION SHEET			Reference No. of Document Being Continued					Page 5 of 24	
	CONTIN	UATION	SHEET	PIIN/SIIN	<b>√</b> ₩56HZ	V-04-P-1052	MOD	/AMD		
Name	of Offeror or	Contractor	HUPP INDUST	RIES						
CONTRAC	T ADMINISTRA	TION DATA								
LINE	PRON/ AMS CD/	OBLG	ACCOUNTED TO				JOB ORDER	ACCOUNT	ING	OBLIGATED
<u>ITEM</u> 0001AA	MIPR EH4Y1676EH 070011	ACRN STAT  AA 2	97 X4930A	CLASSIFICATION C6D 6D	26FB	S20113	<u>NUMBER</u>	STATION W56HZV	\$	<u>AMOUNT</u> 33,004.80
								TOTAL	\$	33,004.80
SERVICE		L BY ACRN		CLASSIFICATION	0.555	200112	STATI			OBLIGATED  AMOUNT
Army		AA	97 X4930A	26D 6D	26FB	S20113	W56HZ	TOTAL	\$ _ \$	33,004.80

# CONTINUATION SHEET Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 6 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

FRACT CLA	AUSES		
2	52.211-5	MATERIAL REQUIREMENTS	AUG/2000
3	52.219-6	NOTICE OF TOTAL SMALL BUSINESS SET-ASIDE	JUN/2003
4	52.222-19	CHILD LABORCOOPERATION WITH AUTHORITIES AND REMEDIES	JAN/2004
5	52.222-21	PROHIBITION OF SEGREGATED FACILITIES	FEB/1999
6	52.225-13	RESTRICTIONS ON CERTAIN FOREIGN PURCHASES	JAN/2004
7	52.232-33	PAYMENT BY ELECTRONIC FUNDS TRANSFERCENTRAL CONTRACTOR REGISTRATION	OCT/2003
8	52.246-1	CONTRACTOR INSPECTION REQUIREMENTS	APR/1984
9	52.246-2	INSPECTION OF SUPPLIESFIXED PRICE	AUG/1996
10	52.246-23	LIMITATION OF LIABILITY	FEB/1997
11	252.211-7005	SUBSTITUTIONS FOR MILITARY OR FEDERAL SPECIFICATIONS AND STANDARDS	FEB/2003
12	252.225-7001	BUY AMERICAN ACT AND BALANCE OF PAYMENTS PROGRAM	APR/2003
13	252.225-7016	RESTRICTION ON ACQUISITION OF BALL AND ROLLER BEARINGS (Alternate I	DEC/2000
		dated Dec 2000)	
14	252.211-7003	ITEM IDENTIFICATION AND VALUATION	JAN/2004
BE DETER	MINED		

[NOTE: The following clause requires unique item identification marking, or a DoD recognized unique identification equivalent, for all items delivered under the contract for which the Government's acquisition cost (as defined under 'Definitions' below) is \$5,000 or more. Unique item identification marking is also required for items listed in paragraph (c)(1)(ii) of the clause. Unique item identification marking is required for embedded subassemblies, components, and parts if listed in paragraph (c)(1(ii), or if listed elsewhere in the solicitation or resulting contract. In the event that the Government has not yet identified these items or embedded parts, paragraph (c)(1)(ii) will read "TBD" for "to be determined". If these items are identified by the Government before the time proposals are due, an amendment to the solicitation will be issued which identifies them. If not, award will be made on the basis of them not being identified, however the contract may be later modified to include such identification marking. This clause also requires the contractor to report the Government's acquisition cost for each item delivered under the contract. Information concerning these requirements is available at http://www.acq.osd.mil/uid.]

#### (a) Definitions. As used in this clause--

"Automatic identification device" means a device, such as a reader or interrogator, used to retrieve data encoded on machine-readable media.

"Commonly accepted commercial marks" means any system of marking products for identification that is in use generally throughout commercial industry or within commercial industry sectors. Some examples of commonly accepted commercial marks are: EAN.UCC Global Trade Item Number; Automotive Industry Action Group B-4 Parts Identification and Tracking Application Standard, and B-2 Vehicle Identification Number Bar Code Label Standard; American Trucking Association Vehicle Maintenance Reporting Standards; Electronic Industries Alliance EIA 802 Product Marking Standard; and Telecommunications Manufacturers Common Language Equipment Identification Code.

"Concatenated unique item identifier" means— (1) For items that are serialized within the enterprise identifier, the linking together of the unique identifier data elements in order of the issuing agency code, enterprise identifier, and unique serial number within the enterprise identifier; or (2) For items that are serialized within the original part number, the linking together of the unique identifier data elements in order of the issuing agency code, enterprise identifier, original part number, and serial number within the part number.

"Data qualifier" means a specified character (or string of characters) that immediately precedes a data field that defines the general category or intended use of the data that follows.

"DoD recognized unique identification equivalent" means a unique identification method that is in commercial use and has been recognized by DoD. All DoD recognized unique identification equivalents are listed at http://www.acq.osd.mil/uid .

"DoD unique item identification" means marking an item with a unique item identifier that has machine-readable data elements to distinguish it from all other like and unlike items. In addition— (1) For items that are serialized within the enterprise identifier, the unique identifier shall include the data elements of issuing agency code, enterprise identifier, and a unique serial number. (2) For items that are serialized within the part number within the enterprise identifier, the unique identifier shall include the data elements of issuing agency code, enterprise identifier, the original part number, and the serial number. Enterprise means the entity (i.e., a manufacturer or vendor) responsible for assigning unique item identifiers to items.

"Enterprise identifier" means a code that is uniquely assigned to an enterprise by a registration (or controlling) authority.

"Government's unit acquisition cost" means-- (1) For fixed-price type line, subline, or exhibit line items, the unit price

## Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

MD

Page 7 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

identified in the contract at the time of delivery; and (2) For cost-type line, subline, or exhibit line items, the Contractor's estimated fully burdened unit cost to the Government for each item at the time of delivery.

"Issuing agency code" means a code that designates the registration (or controlling) authority.

"Item" means a single hardware article or unit formed by a grouping of subassemblies, components, or constituent parts required to be delivered in accordance with the terms and conditions of this contract.

"Machine-readable" means an automatic information technology media, such as bar codes, contact memory buttons, radio frequency identification, or optical memory cards.

"Original part number" means a combination of numbers or letters assigned by the enterprise at asset creation to a class of items with the same form, fit, function, and interface.

"Registration (or controlling) authority" means an organization responsible for assigning a non-repeatable identifier to an enterprise (i.e., Dun & Bradstreet's Data Universal Numbering System (DUNS) Number, Uniform Code Council (UCC)/EAN International (EAN) Company Prefix, or Defense Logistics Information System (DLIS) Commercial and Government Entity (CAGE) Code).

"Serial number within the enterprise identifier or unique serial number" means a combination of numbers, letters, or symbols assigned by the enterprise to an item that provides for the differentiation of that item from any other like and unlike item and is never used again within the enterprise.

"Serial number within the part number or serial number" means a combination of numbers or letters assigned by the enterprise to an item that provides for the differentiation of that item from any other like item within a part number assignment.

"Serialization within the enterprise identifier" means each item produced is assigned a serial number that is unique among all the tangible items produced by the enterprise and is never used again. The enterprise is responsible for ensuring unique serialization within the enterprise identifier.

"Serialization within the part number" means each item of a particular part number is assigned a unique serial number within that part number assignment. The enterprise is responsible for ensuring unique serialization within the part number within the enterprise identifier.

"Unique item identification" means marking an item with machine-readable data elements to distinguish it from all other like and unlike items.

"Unique item identifier" means a set of data marked on items that is globally unique, unambiguous, and robust enough to ensure data information quality throughout life and to support multi-faceted business applications and users.

"Unique item identifier type" means a designator to indicate which method of uniquely identifying a part has been used. The current list of accepted unique item identifier types is maintained at http://www.acq.osd.mil/uid.

- (b) The Contractor shall deliver all items under a contract line, subline, or exhibit line item.
- (c) Unique item identification.
  - (1) The Contractor shall provide DoD unique item identification, or a DoD recognized unique identification equivalent, for-
    - (i) All items for which the Government's unit acquisition cost is \$5,000 or more; and
    - (ii) The following items for which the Government's unit acquisition cost is less than \$5,000:

Contract Line, Subline, or Exhibit Line Item Number: -1-

Item Description: -2-

- (iii) Subassemblies, components, and parts embedded within items as specified in -3-\_\_.
- (2) The unique item identifier and the component data elements of the unique item identifier shall not change over the life of the item.
  - (3) Data syntax and semantics. The Contractor shall--
- (i) Mark the encoded data elements (except issuing agency code) on the item using any of the following three types of data qualifiers, as specified elsewhere in the contract:

## Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 8 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

- (A) Data Identifiers (DIs) (Format 06).
- (B) Application Identifiers (AIs) (Format 05), in accordance with ISO/IEC International Standard 15418, Information Technology-- EAN/UCC Application Identifiers and ASC MH 10 Data Identifiers and ASC MH 10 Data Identifiers and Maintenance.
- (C) Text Element Identifiers (TEIs), in accordance with the DoD collaborative solution ``DD'' format for use until the final solution is approved by ISO JTC1/SC 31. The DoD collaborative solution is described in Appendix D of the DoD Guide to Uniquely Identifying Items, available at http://www.acq.osd.mil/uid; and
- (ii) Use high capacity automatic identification devices in unique identification that conform to ISO/IEC International Standard 15434, Information Technology--Syntax for High Capacity Automatic Data Capture Media.
  - (4) Marking items.
- (i) Unless otherwise specified in the contract, data elements for unique identification (enterprise identifier, serial number, and, for serialization within the part number only, original part number) shall be placed on items requiring marking by paragraph (c)(1) of this clause in accordance with the version of MIL-STD-130, Identification Marking of U.S. Military Property, cited in the contract Schedule.
  - (ii) The issuing agency code--
    - (A) Shall not be placed on the item; and
    - (B) Shall be derived from the data qualifier for the enterprise identifier.
- (d) Commonly accepted commercial marks. The Contractor shall provide commonly accepted commercial marks for items that are not required to have unique identification under paragraph (c) of this clause.
- (e) Material Inspection and Receiving Report. The Contractor shall report at the time of delivery, as part of the Material Inspection and Receiving Report specified elsewhere in this contract, the following information:
  - (1) Description.\*
  - (2) Unique identifier\*\*, consisting of--
    - (i) Concatenated DoD unique item identifier; or
    - (ii) DoD recognized unique identification equivalent.
  - (3) Unique item identifier type.\*\*
  - (4) Issuing agency code (if DoD unique item identifier is used).\*\*
  - (5) Enterprise identifier (if DoD unique item identifier is used).\*\*
  - (6) Original part number.\*\*
  - (7) Serial number.\*\*
  - (8) Quantity shipped.\*
  - (9) Unit of measure.\*
  - (10) Government's unit acquisition cost.\*
  - (11) Ship-to code.
  - (12) Shipment date.
  - (13) Contractor's CAGE code or DUNS number.
  - (14) Contract number.

	Reference No. of Document Being Continued
CONTINUATION SHEET	· ·

PIIN/SIIN W56HZV-04-P-1052 MOD/AMD

Page 9 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

- (15) Contract line, subline, or exhibit line item number.\*
- (16) Acceptance code.
- \* Once per contract line, subline, or exhibit line item.
- \*\* Once per item.
- (f) Material Inspection and Receiving Report for embedded subassemblies, components, and parts requiring unique item identification. The Contractor shall report at the time of delivery, as part of the Material Inspection and Receiving Report specified elsewhere in this contract, the following information:
- (1) Unique item identifier of the item delivered under a contract line, subline, or exhibit line item that contains the embedded subassembly, component, or part.
  - (2) Unique item identifier of the embedded subassembly, component, or part, consisting of-
    - (i) Concatenated DoD unique item identifier; or
    - (ii) DoD recognized unique identification equivalent.
  - (3) Unique item identifier type.\*\*
  - (4) Issuing agency code (if DoD unique item identifier is used).\*\*
  - (5) Enterprise identifier (if DoD unique item identifier is used).\*\*
  - (6) Original part number. \*\*
  - (7) Serial number.\*\*
  - (8) Unit of measure.
  - (9) Description.
- \*\* Once per item.
- (g) The Contractor shall submit the information required by paragraphs (e) and (f) of this clause in accordance with the procedures at http://www.acq.osd.mil.uid
- (h) Subcontracts. If paragraph (c)(1)(iii) of this clause applies, the Contractor shall include this clause, including this paragraph (h), in all subcontracts issued under this contract.

[End of Clause]

15 52.204-4006 INCORPORATION OF TACOM MASTER SOLICITATION FOR SIMPLIFIED MAY/2000 (TACOM) ACQUISITIONS AND DESIGNATION OF F.O.B. POINT

- (a) This Request for Quotation (RFQ) or Purchase Order (PO) incorporates by reference TACOM-Warren's Master Solicitation for Simplified Acquisitions with the same force and effect as though the clauses and provisions it contains were physically incorporated into this document. The version in effect at time of award is the version that applies to your purchase order.
- (b) The TACOM-Warren Master Solicitation for Simplified Acquisitions is available on our Electronic Contracting web page, which you can reach using the following URL address: http://contracting.tacom.army.mil/opportunity.htm
- (c) The clauses and provisions in Section I of the Master Solicitation apply to all TACOM-Warren RFQs and Purchase Orders that contain this clause. The clauses contained in Section II of the Master Solicitation applies in addition to those in Section I when the RFQ or PO specifies F.O.B. Origin.
  - (d) We hereby specify that the required F.O.B. point for this acquisition is DESTINATION.
- (e) We will keep the Master Solicitation identified in this clause available on our Electronic Contracting web page during the entire period of performance of the purchase order. If the current Master Solicitation later is revised to incorporate a change in any of the clauses, the version specified in this clause will be retained, intact, in an archive area on our web page for continued

# Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 10 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

reference and use.

[End of Clause]

16 52.211-4015 (TACOM)

CONFIGURATION CONTROL--ENGINEERING CHANGES

JUL/2002

#### (a) DEFINITIONS:

- (1) Engineering Change Proposal (ECP). An ECP is a suggestion that we (the Government) permanently change some requirement of the Technical Data Package (TDP). ECPs can be issued before or during contract performance. NOTE: The current Government Standard allows us ninety days to process routine ECPs. If you (the contractor) need a response in less than ninety days to meet contract requirements, you should consider submitting a deviation along with your ECP.
- (2) Request for Deviation (RFD). A RFD is a one-time request to deviate from TDP requirements. You must submit your deviation request before you deviate from the TDP requirements. You can request a deviation for a specific number of parts or the entire contract quantity.
  - (3) Value Engineering Change Proposal (VECP). A proposal that --
    - (i) Requires a change to the instant contract; and
- (ii) Results in reducing the overall projected cost to the agency without impairing essential functions or characteristics; provided, that it does not involve a change --
  - (A) In deliverable end item quantities only;
  - (B) In research and development (R&D) end items or R&D test quantities that is due solely to results of previous testing under this contract; or
  - (C) To the contract type only.
  - (4) Notice of Revision (NOR). A NOR describes the proposed changes to a technical document being requested by an ECP.
- (b) When will TACOM start processing change requests? TACOM won't start processing any ECP, VECP, or RFD until we receive the ACO's comments (see paragraph (e) below) and the ECP, VECP, or RFD documentation.
- (c) Contractor Responsibility. ECPs, VECPs, and RFD shall contain information per the instructions outlined on the Data Delivery Descriptions (DDDs) which can be found at the following website: http://contracting.tacom.army.mil/engr/engrchange.htm. Forms for preparing an ECP, VECP, or a RFD can also be found at this website. You may use other media, as long as you give us all the information outlined in the DDDs.
  - (1) Identify the two-digit Weapon System Code (WSC) on your submittal. The WSC for this procurement is N5.
- (2) The Contractor shall submit ECPs/VECPs/RFDs to the Government electronically. You must use one of the following electronic mediums: 100 megabyte Zip\*-disk, 3 1/2 inch disk, 650 megabyte CD ROM, or E-mail. (E-mail files must be sized 3.5 mb or less.) Identify the software application, and version, that you used to create each file submitted.
- (3) ECPs/VECPs/RFDs submitted in paper form are unacceptable and will be returned. You must use one of the following electronic formats:
- (i) Files readable using these Microsoft 97 Office Products: Word, Excel, PowerPoint, or Access. Spreadsheets must be sent in a file format that includes all formulae, macro and format information. Print image is not acceptable.
  - (ii) Files in Adobe PDF (Portable Document Format).
- (iii) Files in HTML (Hypertext Markup Language). HTML documents must not contain active links to live Internet sites or pages. All linked information must be contained within your electronic ECPs/VECPs/RFDs and be accessible offline.
- (iv) Other electronic formats. Before preparing your ECPs, VECPs or RFDs in any other electronic format, please e-mail the engineer, copy-furnished to the buyer and ACO, to obtain a decision as to the format's acceptability. Failure to e-mail the engineer to seek an alternate format's acceptability may result in rejection of your submission. All alternate methods must be at no cost to the Government. NOTE: The above formats may be submitted in compressed form using self-extracting files.

CONTINUATION SHEET	Reference No. of Document Be	Page 11 of 24	
CONTINUATION SHEET	PIIN/SIIN W56HZV-04-P-1052	MOD/AMD	

Name of Offeror or Contractor: HUPP INDUSTRIES

- (d) Submittal Procedures for ECPs/VECPs/RFDs.
  - (1) Send one copy of the ECP, VECP or RFD in electronic format to your ACO.
  - (2) Send one copy of the ECP, VECP or RFD in electronic format to the buyer listed on the solicitation/ contract document.

WARNING - Submit complete, legible, virus free packages per paragraphs 1 and 2 above, or we may return your ECP/VECP/RFD without processing them.

(e) ACO Responsibility. Within ten working days from the day you receive the contractor's request, the ACO must prepare Comments on the ECP, VECP, or RFD in electronic format, and forward it as follows:

ECPs, VECPs, and RFDs. Email a copy of the contractor's request and ACO comments (DD Form 1998) to the engineer (-2-) and the buyer identified in block 7 of the solicitation cover sheet (SF 33), block 5 on the Standard Form 26, or block 6 on the DD Form 1155.

- (f) Approval of ECPs, VECPs and RFDs.
- (1) ECPs should be used to make permanent changes in the Government Technical Data Package (TDP). Contractual relief should be requested using a Request for Deviation. This is because the Government requires more time to analyze any proposal to permanently change the specification or TDP. Cost saving improvements to the TDP should be submitted as a VECP, if a VE clause is contained in the contract.
- (2) ECPs. TACOM will review and make a decision within the ninety day timeframe. Notification of our decision will be made by the contracting officer or representative.
  - (3) RFDs. Decision on RFDs will be made within 30 days from the date we receive them from the ACO.
- (g) Processing Emergency and Urgent ECPs. Ordinarily, ECPs submitted by the contractor will be deemed routine. If you submit an ECP that you consider to be an emergency or urgent (as defined in paragraph 11 of DDD for ECPs), you must immediately notify the PCO. TACOM will review the criticality of the ECP, and, if we determine that it is urgent or critical, we'll follow the appropriate processing time-frames as outlined in paragraph 11 of the DDD for ECPs.
- (h) Reminder Only the PCO can change the Contract. NO OTHER GOVERNMENT REPRESENTATIVE is authorized to make a commitment for, or bind the Government.
  - (i) RFDs shall contain sufficient pricing data to determine if a downward equitable adjustment to the contract is required.
  - (j) Questions.
- (1) Questions about preparation and submittal of change request should be directed to the Government Quality Assurance Representative (OAR).
- (2) Questions about the status of change requests you've already submitted, contact the buyer. You can find the buyer's name, number and e-mail address in block 7 of the solicitation cover sheet (SF 33), block 5 on the Standard Form 26, or block 6 on the DD Form 1155

[End of Clause]

17 52.211-4053 REQUIRED TAILORING LANGUAGE TO ELIMINATE CLASS I OZONE-DEPLETING MAR/2000 (TACOM) SUBSTANCES

- (a) The purchase description or Technical Data Package (TDP) for this purchase order incorporates one or more specifications or standards that, in their unmodified form, either authorize or require the use of Class I Ozone-Depleting Substances (CIODS). For purposes of your performance on this purchase order, those specifications (which are identified in paragraph (b) of this clause) are modified by special tailoring language which appears in the TACOM Acquisition Center's web-site. Directions for reaching our web-site and locating the required tailoring language appear in paragraph (c) of this clause.
- (b) Tailoring language to eliminate the authorization or requirement to use Class I Ozone-Depleting Substances (CIODS) is hereby incorporated into this contract by reference. Packaging Specifications MIL-L-61002 and MIL-STD-129, where they apply, are affected by this tailoring language. Other specifications and standards affected are: MIL-DTL-53072
- (c) The CIODS listing that contains the required tailoring language is on the TACOM Acquisition Center web-site, which you can reach by using this URL: http://contracting.tacom.army.mil/ciods.html

# CONTINUATION SHEET Reference No. of Document Being Continued Page 12 of 24 PIIN/SIIN W56HZV-04-P-1052 MOD/AMD

Name of Offeror or Contractor: HUPP INDUSTRIES

[End of Clause]

18 52.217-4001 SEPARATELY PRICED OPTION FOR INCREASED QUANTITY APR/1997 (TACOM)

- (a) The Government hereby reserves the right to increase the quantity of the contract item up to an additional quantity of 432 units. The unit price for such option quantity shall be as set forth in CLIN 0002AA. This option may be exercised by the Government at any time, but in any event not later than 90 days after DATE OF AWARD. In addition, such option may be exercised in increments, subject to the stated total additional quantity limitations, price(s), and the above-stated time for exercise of the option.
- (b) Delivery of the items added by the exercise of this option shall continue immediately after, and at the same rate as, delivery of like items called for under this contract, unless the parties hereto otherwise agree.
- (c) Additionally, prior to the expiration of the original option period identified in paragraph (a) above, the Government may seek a bilateral extension of the option period for an additional period not to exceed 90 days from the expiration date of the original option period.

[End of Clause]

19 52.246-4005 INSPECTION AND ACCEPTANCE POINTS: ORIGIN FEB/1995 (TACOM)

- (a) Inspection and acceptance of supplies offered under this purchase order shall take place as specified herein. Inspection: ORIGIN Acceptance: ORIGIN
  - (b) Origin inspection shall take place at the site specified below:

HUPP AEROSPACE/DEFENSE 1690 SUMMIT STREET NEW HAVEN, IN 46774

[End of Clause]

20 52.246-4053 USE OF MIL-STD 1916 JAN/2001 (TACOM)

The Government will not accept lots whose samples submitted for acceptance contain nonconformances unless appropriately documented and approved by the contracting officer. The contractor shall use MIL-STD- 1916, DOD Preferred Methods of Acceptance of Product. The Verification Level (VL) shall be VL IV for major characteristics and VL II for minor characteristics. MIL-HDBK-1916 provides guidance on the use of MIL-STD 1916. This handbook is not contractually binding.

[End of Clause]

21 52.222-25 AFFIRMATIVE ACTION COMPLIANCE APR/1984

The offeror represents that

(1) It [ ] has developed and has on file
 [ ] has not developed and does not have on file,

at each establishment, affirmative action programs required by the rules and regulations of the Secretary of Labor (41 CFR 60-1 and 60-2), or

(2) It [ ] has not previously had contracts subject to the written affirmative action programs requirement of the rules and regulations of the Secretary of Labor.

[End of Provision]

# CONTINUATION SHEET Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052 MOD/AMD

Page 13 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

(a) If this contract is awarded on an f. o. b. destination basis, and if transportation is accomplished by common carrier, parcel post, or other than common carrier, the Contractor agrees not to invoice until the supplies are shipped, and to retain the following evidence of shipment (EOS) documentation for a period of 4 years after completion of the contract.

- (1) If transportation is accomplished by common carrier, the Contractor will retain a signed copy of the commercial bill of lading of the supplies covered by the invoice, indicating the carrier's intent to ship said supplies to the destination specified in the contract.
  - (2) If transportation is accomplished by parcel post, the Contractor will retain a copy of the mailing certificate, or
- (3) If transportation is by other than common carrier or parcel post, the Contractor will retain the receipt copy of the appropriate delivery document showing receipt at the destination in the contract.
- (b) Retention of the above EOS documentation and having the documentation available for subsequent review, if needed, eliminates the requirement to provide these documents with the Contractor's paper, or electronically transmitted, invoices.

[End of Clause]

23 252.223-7001 HAZARD WARNING LABELS

DEC/1991

- (a) <u>Hazardous material</u>, as used in this clause, is defined in the Hazardous Material Identification and Material Safety Data clause of this contract.
- (b) The Contractor shall label the item package (unit container) of any hazardous material to be delivered under this contract in accordance with the Hazard Communication Standard (29 CFR 1910.1200 et seq). The Standard requires that the hazard warning label conform to the requirements of the standard unless the material is otherwise subject to the labelling requirements of one of the following statutes:
  - (1) Federal Insecticide, Fungicide and Rodenticide Act;
  - (2) Federal Food, Drug and Cosmetics Act;
  - (3) Consumer Product Safety Act;
  - (4) Federal Hazardous Substances Act; or
  - (5) Federal Alcohol Administration Act.
- (c) The Offeror shall list which hazardous material listed in the Hazardous Material Identification and Material Safety Data clause of this contract will be labelled in accordance with one of the Acts in paragraphs (b)(1) through (5) of this clause instead of the Hazard Communication Standard. Any hazardous material not listed will be interpreted to mean that a label is required in accordance with the Hazard Communication Standard.

MATERIAL (If None, Insert None.)	<u>ACT</u>

- (d) The apparently successful Offeror agrees to submit, before award, a copy of the hazard warning label for all hazardous materials not listed in paragraph (c) of this clause. The Offeror shall submit the label with the Material Safety Data Sheet being furnished under the Hazardous Material Identification and Material Safety Data clause of this contract.
- (e) The Contractor shall also comply with MIL-STD-129, Marking for Shipment and Storage (including revisions adopted during the term of this contract).

[End of Clause]

24 252.247-7023 TRANSPORTATION OF SUPPLIES BY SEA (Alternate III dated May 2002) MAY/2002

## Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 14 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

- (1) Components means articles, materials, and supplies incorporated directly into end products at any level of manufacture, fabrication, or assembly by the Contractor or any subcontractor.
  - (2) Department of Defense (DoD) means the Army, Navy, Air Force, Marine Corps, and defense agencies.
  - (3) Foreign flag vessel means any vessel that is not a U.S.-flag vessel.
  - (4) Ocean transportation means any transportation aboard a ship, vessel, boat, barge, or ferry through international waters.
- (5) Subcontractor means a supplier, materialman, distributor, or vendor at any level below the prime contractor whose contractual obligation to perform results from, or is conditioned upon, award of the prime contract and who is performing any part of the work or other requirement of the prime contract. However, effective May 1, 1996, the term does not include a supplier, materialman, distributor, or vendor of commercial items or commercial components.
- (6) Supplies means all property, except land and interests in land, that is clearly identifiable for eventual use by or owned by the DoD at the time of transportation by sea.
- (i) An item is clearly identifiable for eventual use by the DoD if, for example, the contract documentation contains a reference to a DoD contract number or a military destination.
- (ii) Supplies includes (but is not limited to) public works; buildings and facilities; ships; floating equipment and vessels of every character, type, and description, with parts, subassemblies, accessories, and equipment; machine tools; material; equipment; stores of all kinds; end items; construction materials; and components of the foregoing.
- (7) <u>U.S.-flag vessel</u> means a vessel of the United States or belonging to the United States, including any vessel registered or having national status under the laws of the United States.
  - (b)(1) The Contractor shall use U.S.-flag vessels when transporting any supplies by sea under this contract.
    - (2) A subcontractor transporting supplies by sea under this contract shall use U.S.-flag vessels if-
      - (i) This contract is a construction contract; or
      - (ii) The supplies being transported are-
        - (A) Noncommercial items; or
        - (B) Commercial items that-
  - (1) The Contractor is reselling or distributing to the Government without adding value (generally, the Contractor does not add value to items that it subcontracts for f.o.b. destination shipment);
  - (2) Are shipped in direct support of U.S. military contingency operations, exercises, or forces deployed in humanitarian or peacekeeping operations; or
  - (3) Are commissary or exchange cargoes transported outside of the Defense Transportation System in accordance with 10 U.S.C. 2643.
- (c) The Contractor and its subcontractors may request that the Contracting Officer authorize shipment in foreign-flag vessels. or designate available U.S.-flag vessels, if the Contractor or a subcontractor believes that--
  - (1) U.S.-flag vessels are not available for timely shipment;
  - (2) The freight charges are inordinately excessive or unreasonable; or
  - (3) Freight charges are higher than charges to private persons for transportation of like goods.
- (d) The Contractor must submit any request for use of other than U.S.-flag vessels in writing to the Contracting Officer at least 45 days prior to the sailing date necessary to meet its delivery schedules. The Contracting Officer will process requests submitted after such date(s) as expeditiously as possible, but the Contracting Officer's failure to grant approvals to meet the shipper's sailing date will not of itself constitute a compensable delay under this or any other clause of this contract. Requests shall contain at a minimum--
  - (1) Type, weight, and cube of cargo;
  - (2) Required shipping date;
  - (3) Special handling and discharge requirements;
  - (4) Loading and discharge points;
  - (5) Name of shipper and consignee;

# Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 15 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

- (6) Prime contract number; and
- (7) A documented description of efforts made to secure U.S.-flag vessels, including points of contact (with names and telephone numbers) with at least two U.S.-flag carriers contacted. Copies of telephone notes, telegraphic and facsimile message or letters will be sufficient for this purpose.
- (e) The Contractor shall, within 30 days after each shipment covered by this clause, provide the Contracting Officer and the Division of National Cargo, Office of Market Development, Maritime Administration, U.S. Department of Transportation, Washington, DC 20590, one copy of the rated on board vessel operating carrier's ocean bill of lading, which shall contain the following information-
  - (1) Prime contract number;
  - (2) Name of vessel;
  - (3) Vessel flag of registry;
  - (4) Date of loading;
  - (5) Port of loading;
  - (6) Port of final discharge;
  - (7) Description of commodity;
  - (8) Gross weight in pounds and cubic feet if available;
  - (9) Total ocean freight in U.S. dollars; and
  - (10) Name of the steamship company.
- (f) The Contractor shall insert the substance of this clause, including this paragraph (f) in subcontracts that are for a type of supplies described in paragraph (b)(2) of this clause.

[End of Clause]

25 52.204-4005 REQUIRED USE OF ELECTRONIC CONTRACTING (TACOM)

DEC/2002

- (a) All contract awards, modifications and delivery orders issued by TACOM will be issued electronically. The contractor has the option to receive these actions either via the Worldwide Web (WWW) or Electronic Data Interchange (EDI). Many provisions/clauses that appear "by reference", meaning only clause titles and regulation site are listed; their full texts can be found at the website http://farsite.hill.af.mil/
- (b) In order to be eligible to receive an award under this solicitation, the successful offeror must be registered with the Department of Defense (DOD) Central Contractor Registration (CCR). The CCR registration process may be done electronically at the World Wide Web (WWW) site: http://www.ccr.gov/. (In order to be registered to use EDI, you must use the long form for registration. Certification information, including information on the EDI 838 TPP, must be furnished to the Contracting Officer within 60 calendar days after contract award to complete networking requirements within the Government.)
- (c) Worldwide Web Distribution. The contractor will receive an electronic Notice of the Award, Modification, or Delivery Order via e-mail. If you choose the WWW option, you must download the file from the appropriate TACOM webpage:

Warren: http://contracting.tacom.army.mil/awards\_official.htm
Rock Island: http://aais.ria.army.mil/AAIS/AWDINFO/index.htm
Picatinny: http://procnet.pica.army.mil/Contracts/Index.htm
Red River Army Depot: http://www.redriver.army.mil/contracting/Awards
Anniston Army Depot: http://www.anadprocnet.army.mil

- (d) Electronic Data Interchange. If you choose to receive contract awards, modifications and delivery orders through EDI, they will be delivered electronically via the Federal Acquisition Network (FACNET). Federal Standard Version 3050 of Standard X12 from the American National Standards Institute (ANSI) will be used as the format for these electronic transactions.
- (1) You must complete the EDI 838 Trading Partner Profile, and must agree (i) to subcontract with a DoD certified VAN or Value Added Service (VAS) provider, or (ii) to become DoD certified as a Value Added Network (VAN). The EDI 838 Training Partner

## Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 16 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

Profile is contained in the basic CCR registration form and includes portions of the registration form which are titled "Optional".

- (2) You must select a VAN from the official DoD approved list. DoD Certified VANs are listed at http://www.acq.osd.mil/ec/ecip/index.htm . If your VAN is later removed from the official list, or if you voluntarily drop your initially selected VAN, then you must switch to a VAN that remains on the official DoD approved list. You must maintain an active account on a DoD approved VAN for the entire duration of the contract, beginning no later than the 60th day after award.
- (e) Unless otherwise specified elsewhere in the contract, all data items you are required to provide under this contract must be submitted electronically. Acceptable formats include:
  - (1) Microsoft\* 97 Office Products (TACOM can currently read OFFICE 97\* and lower.): Word, Excel, Powerpoint, or Access
  - (2) 100 OR 250 MEGABYTE ZIP\*-DISK, 3 1/2 INCH DISK, OR 650 MEGABYTE CD ROM
    - (3) E-MAIL (Maximum size of each e-mail message is be three and one-half (3.5) megabytes).
- (4) Other electronic formats. Before submitting your data in any other electronic format, please e-mail the buyer identified on the face of the contract, with e-mail copy-furnished to amsta-idq@tacom.army.mil, to obtain a decision as to the format's acceptability. This e-mail must be received by the buyer not later than ten calendar days before the required data submission date.

NOTE: The above formats may be submitted in compressed form using self-extracting files.

(f) Additional information can be obtained by sending a message to: acqcenweb@tacom.army.mil or by calling (586) 574-7059.

[End of Clause]

26 52.204-4007 OFFEROR'S DATAFAX NUMBER, E-MAIL ADDRESS, AND CAGE CODE MAY/2000 (TACOM)

(a) If you have a company data fax number, please provide it on the following line:\_\_\_\_\_\_

(b) If you have a company Internet address that we can use in the future when sending out electronic notices and possibly solicitations, please provide the complete e-mail address on the following line:

(c) Provide your CAGE (Contractor And Government Entity) code here:

[End of Provision]

27 52.204-4008 REQUIRED USE OF ELECTRONIC DATA INTERCHANGE (EDI) MAY/2000 (TACOM)

The Government reserves the right to commence issuing orders to the contract within 90 calendar days after contract award. Any modifications and any delivery orders will be delivered electronically to the contractor using Electronic Data Interchange (EDI) via the Federal Acquisition Network (FACNET). Version 3050 of Standard X12 from the American National Standards Institute (ANSI) will be used as the format for these electronic transactions.

[End of Clause]

28 52.204-4009 MANDATORY USE OF CONTRACTOR TO GOVERNMENT ELECTRONIC COMMUNICATION JUN/1999 (TACOM)

- (a) All references in the contract to the submission of written documentation shall mean electronic submission. All electronic submissions shall be in the formats and media described in the "Electronic Quotations/Offers/Bids Required in Response to this Request for Quotations/Proposals/Bids" clause elsewhere in this document. (See Section K for commercial acquisitions, Section L for RFPs, and Section I for RFOs.)
- (b) This shall include all written unclassified communications between the Government and the Contractor except contract awards and contract modifications which shall be posted on the internet. Return receipt shall be used if a commercial application is available. Classified information shall be handled in full accordance with the appropriate security requirements.

## Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Name of Offeror or Contractor: HUPP INDUSTRIES

(c) In order to be contractually binding, all Government communications requiring a Contracting Officer signature must be sent from the Contracting Officer's e-mail address. The Contractor shall designate the personnel with signature authority who can contractually bind the contractor. All binding contractor communication shall be sent from this contractor e-mail address(es).

- (d) Upon award, the Contractor shall provide the Contracting Officer with a list of e-mail addresses for all administrative and technical personnel assigned to this contract.
- (e) Unless exempted by the Procuring Contracting Officer in writing, all unclassified written communication after contract award shall be transmitted electronically.

[End of Clause]

29 52.211-4008 DRAWING LIMITATIONS (TACOM)

NOV/2002

Page 17 of 24

- (a) The drawings supplied with this contract are <u>not</u> shop or process drawings. They are engineering design drawings. They are adequate to permit manufacture, and:
  - (1) depict the completed (item(s), and
  - (2) serve as the basis for inspection of the completed item(s).
- (b) These drawings DON'T cover intermediate drawings/specifications or steps in the manufacturing process. As a result, even if you meet all the dimensions and tolerances specified in the engineering design drawing for each individual part, a cumulative unacceptable fit for the contract item could result.
- (c) YOU ARE RESPONSIBLE for producing the shop or process drawings needed to cover intermediate steps in the manufacturing process.
- (d) The Contractor agrees that he has obtained all specifications and drawings necessary to manufacture the items being solicited in accordance with the TDP including all incorporated specifications and drawings. The contractor is responsible for having all drawings and specifications. Delivery delays are not excusable where the contractor asserts that it did not have a specification or drawing and has failed to request, in writing, the specification from either the Contracting Officer or Contract Specialist prior to the solicitation closing date.
- (e) If you fail to produce an end item with a cumulative fit that conforms to Government drawings, specifications or other supplemental manufacturing documentation, you'll be responsible for correcting this condition at no additional cost to the Government and no delivery schedule extension.

[End of Clause]

30 52.211-4016 CARC PAINT-PRETREATMENT REQUIREMENTS FOR FERROUS, GALVANIZED AND AUG/2003
ALUMINUM SURFACES

(a) Ferrous and galvanized surfaces shall be cleaned and pretreated with a Type 1 microcrystalline zinc phosphate system per TT-C-Alternate pretreatment systems for ferrous substances must meet the performance tests specified in paragraphs 3.5.7, 3.5.8, 4.2.7, and 4.2.8 of TT-C-490E. Corrosion resistance tests will be conducted on a monthly basis (two test coupons) after the process has been found to be in compliance with the (pretreatment chemicals) manufacturers instructions. Process control tests for this or alternative systems must ensure that the process remains in control and must be documented per ISO 9000 series and approved by TACOM. Testing (corrosion resistance and adhesion) must be performed on the same substrate and the same thickness of primer minus topcoat used Unless otherwise specified, MIL-P-53022 and -53030 primers shall be salt spray tested for 336 hours (ASTM B117). All electrocoat primers shall be tested for 1000 hours. Test coupons shall be scraped at a 30 degree contact angle (approximate), with a one inch (approximate) metal blade such as a putty knife, between 24 and 168 hours after removal from the neutral salt spray cabinet for coupon evaluation. Any TT-C-490E (Type I) inorganic crystalline pretreatment is limited to a maximum build equivalent of 500 mg per square foot to minimize chipping of the CARC system. All TT-C-490E (Type I) zinc phosphate pretreatment systems must be documented per ISO 9000 series and approved by the procuring activity prior to use. The procedure containing all the elements specified in paragraph 3.2 of TT-C-490E shall be submitted to the procuring activity no less than 45 days prior to start of work. Oualification will consist of verification that the process with its controls can meet the performance requirements in the specification. The performance of zinc phosphate or any proposed alternate pretreatment system must be demonstrated and approved by the procuring activity. Prior to production, a Letter of Approval shall be provided by the Contracting Officer.

Requalification of the process shall be required if the process is changed outside the limits defined in the TACOM letter of system acceptance (Letter of Approval) provided to the application facility.

Note: Zinc phosphate systems for galvanized surfaces require separate qualification. Hot dipped galvanized surfaces are highly prone

## Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 18 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

to chlorine/chloride contamination from the galvanizing flux process. This contaminant must be removed prior to pretreatment for the coating system to pass these performance tests. Due to the wide variation in zinc thickness with the hot dip galvanizing process, the dry film thickness of the primer will be verified with a Tooke gage or equivalent for the purpose of production and process control. Primer test coupons shall represent both the minimum and maximum nominal dry film thickness. The test coupons must duplicate the production painting process as closely as possible.

- (b) Qualification of pretreatment systems for zinc galvanized substrates shall be performed using Accelerated Corrosion Test protocol contained in GM 9540P, Method B, rather than salt spray. Test coupons with pretreatment and primer only shall be cured for seven days, and then scribed through the primer to the substrate. After 40 cycles of test exposure, the test coupons shall be scraped at a 30 degree contact angle (approximate), with a one inch (approximate) metal blade such as a putty knife, both parallel and perpendicular to the scribe between 24 and 168 hours after removal from the cyclic salt spray chamber for coupon evaluation. There shall be no more than 3 mm of red rust creep, blistering, or loss of paint adhesion from the scribe line and no more than 5 blisters in the field with none greater than 1 mm diameter. This test shall be performed at two month intervals (two test coupons) to ensure that the process remains in control.
- (c) Aluminum substrates require a chromate conversion coating per MIL-C-5541E (or alternate, see note below), after appropriate cleaning per TT-C-490E. If any other alternate pretreatment is considered, it must pass 120 cycles of GM9540P, as a scribed Q-panel when coated with the production primer. After completion of the cyclic salt environment exposure, the panels shall be scraped as described above, and shall have no more than 0.5 mm paint loss (creep-back) from the scribe. In addition, there shall be no more than After completion of the 120 cycle corrosion resistance test evaluation, 5 blisters in the field with none larger than 1mm diameter. each test panel will be subjected to cross hatch tape test (ASTM D3359, minimum tape adhesion rating of 45 oz. per inch of width). test pattern shall be 4 lines x 4 lines scribed to the metallic layer at 2mm intervals (approximate) and shall be done no closer than 12 mm from any panel edge or the scribe. Multiple head cutters may be used. The removal of two or more complete squares of primer shall constitute failure. Any alternate system must demonstrate its ability to pass both corrosion and adhesion tests on 5 consecutive days of production to be considered acceptable. All process steps shall be documented IAW ISO 9000 series standards and approved by the procuring activity.

Note: The only alternative products which have demonstrated their ability to meet these requirements for 5000 and 6000 series aluminum alloys are Alodine 5200 and Alodine 5700.

(d) The use of TT-C-490E Type III: Vinyl Wash Primer (DOD-P-15328) is prohibited due to its hexavalent chromium content and high VOC level. The Army is committed to minimizing the use of HAPs and hazardous materials.

[End of Clause]

- ENHANCED CARC REQUIREMENTS FOR HIGH PERFORMANCE SYSTEMS JUN/2002 31 52.211-4017 (a) THE FOLLOWING REQUIREMENTS SUPERSEDE THE PERFORMANCE REQUIREMENTS CONTAINED IN TT-C-490, MIL-C-5541 AND MIL-C-53072 RELATIVE TO THE ADHESION AND CORROSION RESISTANCE OF THE CARC SYSTEM:
- (b) Ferrous and galvanized surfaces shall be cleaned and pretreated to provide the following level of performance on a repeatable basis. The cleaning/pretreatment/control process shall be documented and submitted to the procuring activity for approval prior to production. Qualification and process control testing shall be performed on the same substrate used in production. The system under
- test shall consist of the pretreatment and primer. There are significant variations in performance due to primer manufacturer, VOC content and primer thickness variation. Sufficient testing shall be conducted to achieve a statistical confidence in both the brand/type of primer used and the dry film thickness used in production. If the tolerance of the dry film thickness exceeds plus or minus 1.0 mil then you must qualify the extremes of the range separately.
- (c) To verify the corrosion resistance, a minimum of three test panels per test variation no smaller than 4 x 12 inches with the pretreatment/primer system as noted above shall be subjected to 1000 hr. of neutral salt spray per ASTM B117 (40 cycles of GM 9540P scribed is the preferred alternative) for ferrous substrates or 40 cycles of GM 9540P for galvanized surfaces. The test panels shall be cured for a minimum of 7 days and vertically scribed through the coating system to the metallic layer. A minimum of 24 hr. after the completion of the neutral salt spray test or within 5 days after completion of the GM 9540P test the scribe shall be scraped at a 30 degree (approximate) contact angle with a 38mm (approximate) blunt tipped metal blade such as a putty knife parallel and perpendicular to the scribe. There shall be no more than 3mm maximum loss of paint adhesion or corrosion at any point from the scribe line. In addition, there shall be no more than 5 blisters in the field with none exceeding 1mm; corrosion in the field shall not exceed Rust Grade 9 of ASTM D610. The minimum primer dry film thickness noted on the test panels which pases the corrosion resistance test shall be the minimum requirement for production painted hardware.
- (d) To verify long term CARC adhesion, after completion of the corrosion resistance test evaluation each test panel will be subjected to cross hatch tape test (minimum tape adhesion rating of 45 oz. per inch of width). The test pattern shall be 4 x 4 scribe lines to the metallic layer at 2mm intervals(approximate) and shall be done no closer than 12 mm from any edge or the scribe creep. Multiple head cutters are not recommended. Loss of two or more complete primer squares shall constitute failure.
  - (e) The contractor must demonstrate the ability to pass both tests for the system to be considered acceptable. This testing shall

## Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 19 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

be performed on 5 consecutive days of production. If all test panels are acceptable, the testing can revert to two test panels every two months of production.

(f) The only system that is currently available to achieve this level of performance is a zinc phosphate pretreatment system per TT-C-490 with a high quality primer. All primers used must be on the QPL for MIL-P-23377, 53022, -53030, or 53084. Not all QPL primers with the exception of electrocoat primers per MIL-C-53084 have this level of corrosion resistance/paint adhesion, however. New high performance, "Combat Grade" Powder Coat Primers will also meet this performance requirement. These primers can only be applied by approved applicators. The Specification controlling both the primers and their application are available upon request from AMSTA-TR-E/MEPS, (586) 574-5083.

Note: Hot dipped galvanized surfaces are highly prone to chlorine/chloride contamination from the galvanizing flux process. This contaminant must be removed for the coating system to pass these performance tests.

- (g) For aluminum substrates the required pretreatment system is a chromate conversion per MIL-C-5541. If alternative pretreatment systems wish to be considered, they must demonstrate their ability to pass when coated with the nominal production primer (scribed) 120 cycles of GM 9540P. After completion of the test, the panels shall be scraped as noted above and shall have no more than 0.5mm of paint loss maximum from the scribe. In addition, there shall be no more than 5 blisters in the field with none larger than 1mm. After completion of the 120 cycle test, the cross hatch scribe test noted above shall be performed. The removal of one or more complete squares of primer shall constitute failure. The alternate system must demonstrate its ability to provide an acceptable product on 5 consecutive days of production to be considered a suitable alternative. The alternative process must be documented and approved by the procuring activity. Controls must be established to assure that the process remains under statistical control. The only alternative products which have demonstrated their ability to meet these requirements for 5000 and 6000 series aluminum alloys are Alodine 5200 and Alodine 5700.
- (h) Failure to meet the corrosion resistance/adhesion requirements shall be cause for rejection of all production units manufactured during that production interval.
- (i) Final Acceptance of the CARC Finish on Production Hardware:

The dry film thicknesses of the primer and topcoat as well as coating adhesion on the fully cured primer/topcoat coating system are mandatory requirements. Variations in the primer thickness and curing conditions will dramatically affect recoat windows and coating performance for some primers. Manufacturing processes which are unable to control the dry film thickness to the requirements contained in Table V of MIL-C-53072 shall be subjected to the 4 x 4 cross hatch scribe test noted above on two production units per lot with two tests per unit. One test shall be conducted on a vertical and one on a horizontal surface (relative to the painting process). There shall be a maximum removal of one complete square of primer/topcoat or topcoat only. The polyurethane CARC topcoat requires approximately 24 days to completely cure at 68 Degrees F. To accelerate the curing for purposes of product acceptance, the following procedure may be followed: Cure at 190-210 degrees F for three hours (this is time at temperature and is, therefore, material thickness dependent) once the topcoat has reached a dry-to-touch condition. This is to be followed by 7 days at 65 degrees F minimum. Adhesion testing shall be performed only on a completely cured CARC finish. Contractors which have performed a thorough design of experiments methodology to evaluate the impact of paint system variables or have processes which meet Table V requirements can perform the final acceptance adhesion test on representative test coupons.

[End of Clause]

32 52.211-4030 SPECIAL TESTING REQUIREMENTS FOR CHEMICAL AGENT RESISTANT COATINGS MAR/2001

> (CARC) ON METALLIC SURFACES (TACOM)

(a) Application: MIL-C-46168 MIL-C-53039

MIL-PRF-22750

- (b) End-Item Paint Inspection: After the complete paint finish has been applied and cured\* (See \*Note, below), the Contractor shall test and inspect two units per lot for (i) workmanship, (ii) total paint film thickness, and (iii) paint adhesion. Unless otherwise agreed to between the Contractor and the cognizant Government quality assurance representative, a  $\underline{lot}$  shall be defined as all units submitted for final Government acceptance at one time. The use of test panels in lieu of actual production units is prohibited. At final inspection, the cumulative total paint film thickness of pretreatment, primer, and topcoat shall at a minimum conform to the sum of the minimum thicknesses for individual elements of the paint finish as specified in the Film Thickness Table below. Sufficient locations shall be spot-checked to ensure proper workmanship and paint thickness uniformity. The size and configuration of the unit as well as the number of vendors responsible for the paint finish of component parts shall be taken into consideration in determining the number of locations to be checked. The specific number of test locations shall be agreed to by the cognizant Government quality assurance representative in advance. In addition, two locations on each sample unit shall be selected to conduct the scribe tape test. The test locations shall be routinely varied among the following:
  - (1) Directly adjacent to a weld
  - (2) On or directly adjacent to a machine cut or sheared edge.

CONTINUATION SHEET	Reference No. of Document Being Continued	Page 20 of 24
CONTINUATION SHEET	PIIN/SIIN W56HZV-04-P-1052 MOD/A	MD

Name of Offeror or Contractor: HUPP INDUSTRIES

- (3) On any mechanically formed surface when lubricants/drawing compounds were used.
- (4) On paint touch-up areas.
- (c) The precise location for each scribe tape test shall be in an inconspicuous location that has been accepted by the cognizant Government quality assurance representative before the test is conducted.
- (d) Upon completion of the scribe tape test, the scribe marks shall be feathered into the adjacent area and touched up with the required top coat so that the tested area again conforms to the applicable minimum specified in the Film Thickness Table below.

\*Note: The complete paint finish is defined as the pretreatment, primer, and topcoat applied to the substrate. Curing of the complete paint finish is dependent upon temperature, humidity, and paint film thickness. The time necessary to achieve sufficient adhesion to pass the scribe tape test must be determined by each facility. For purposes of this test, curing at ambient temperature will take from 24 days.

#### (e) <u>Test Methods</u>:

- (1) <u>Film Thickness</u>. Film thickness shall be verified with a nondestructive film gage. The gage shall be suitable for measurements over the applicable substrate material and shall have sufficient accuracy to ensure compliance to the thickness limitations. The gage shall be capable of being calibrated. If no other calibration specification or requirement is identified elsewhere in this contract, then the gage shall be calibrated in accordance with ISO 10012.
- (2) <u>Scribe Tape Test</u>. The following test procedure shall be followed. The test surface shall be sufficiently warm and dry to ensure adhesion of the tape. All dimensions cited in this Scribe Tape Test description are approximate:
- (i) Scribe four one-inch lines completely through the paint finish to the substrate, one sixteenth to three thirty-seconds of an inch apart.
- (ii) Scribe four additional one-inch lines, completely through the paint finish, one sixteenth to three thirty-seconds of an inch apart, rotated 90 degrees with respect to the first set of lines. The resulting pattern shall contain nine squares.
- (iii) Press a length of A-A-1830, A-A-884, or any commercially available tape with a minimum adhesion rating of 45 oz. per inch of width firmly over the scribed pattern, rubbing out all air pockets.
- (iv) Wait 10 seconds, minimum. Grasp a free end of the tape and at a rapid speed strip it from the paint surface by pulling the tape back upon itself at 180 degrees.

#### (f) <u>Interpretation of Test Results</u>

NOTE: These two tests are not a substitute for corrosion tests such as neutral salt spray or accelerated corrosion tests which verify coating durability.

(1) Film Thickness. All applicable surfaces shall have complete paint coverage. A minimum of 75% of the applicable surfaces of each test unit shall meet the minimum, cumulative dry film thickness requirements. Failure of either test unit shall result in rejection of the production lot that it represents.

#### FILM THICKNESS TABLE

SPECIFICATION	DRY FILM THICKNESS (Mils)
DOD-P-15328*	0.3 - 0.5
MIL-PRF-23377	1.0 - 1.5
MIL-P-53022	1.0 - 1.5
MIL-PRF-22750	1.3 - 1.7
MIL-P-53030	1.0 - 1.5
MIL-C-46168	1.8 - 3.2
MIL-C-53039	1.8 - 3.2

<sup>\*</sup>May not be allowed per contract due to VOC and hexavalent chromium content.

# Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 21 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

(2) Scribe Tape Test (Adhesion). The removal of two or more complete squares of top coat, or top coat-primer-pretreatment coating, from either test unit constitutes test failure and the production lot from which it comes is rejected. Removal of overspray does not constitute test failure.

Notice: The scribe tape test is designed to detect any deficiency in the paint application process that would affect the durability of the CARC finish. Typical causes of failure are:

- (i) Inadequate cleaning of the substrate.
- (ii) Contamination of the surface between coatings.
- (iii) Excessive paint film thickness in a single coating application.
- (iv) Application of a coating over a previous coating which has not been adequately cured.

It is strongly recommended that the Contractor implement rigid in-process controls in conjunction with the best industrial painting practices to ensure that the performance requirements specified in this clause are met.

[End of Clause]

33 52.215-4404 DATA A

DATA AND COMMUNICATIONS SUBMITTED TO THE GOVERNMENT ELECTRONICALLY

MAY/2002

MAR/2000

- (TACOM)
- (a) The Government often employs contractors as system administrators to operate and maintain Government computer systems. These systems include local area networks, web sites, databases, other electronic records, e-mail accounts, other electronic data transfer mechanisms and computer software. The employees of these contracted system administrators sign nondisclosure agreements obligating them not to reveal information contained in files, documents, computers or systems that they administer. However, unless such information is protected in some way, contracted system administrators do have the ability to access such information.
- (b) Potential contractors as well as any other parties are thus advised to take steps needed to prevent access by contracted system administrators to information submitted electronically to the Government. Absent such steps, it is assumed that contracted system administrators are permitted the capability to access the data. The access will be limited to that which is necessary for the contract system administrator to perform its duties for the Government. The access shall be subject to the condition that third party information is not to be revealed by the contracted system administrator.

[End of Clause]

34 52.246-4025

HIGHER-LEVEL CONTRACT QUALITY REQUIREMENT -- TACOM QUALITY SYSTEM

(TACOM) REQUIREMENT

- (a) This solicitation will result in a purchase order that will require the contractor to use a quality-assurance system to ensure the quality of the purchased items.
- (b) To allow TACOM to analyze your proposed quality system, especially if that system is not based on a national or international standard, you must identify your system as part of your response to this solicitation. Paragraph f (below) asks you to identify what quality-assurance system you will use.
- (1) If you indicate that your quality system conforms to one of the ISO 9000-series standards, or to QS 9000, or to ANSI/ASQ 9001 or 9002, this is a sufficient description: you need not further describe your quality system in your response to the solicitation.
- (2) If your quality system does not conform to any of the standards listed in (b)(1) immediately above, then in addition to identifying the name of the quality system you intend to use, you also must provide a description of your proposed system, in enough detail to let us assess its suitability for use in performing the resulting order. This is of particular importance if your proposed system is unique, using quality control methods and techniques that your company has developed in-house. (Note, however, that if the quality system you intend to use is one that conforms to MIL-Q-9858, MIL-I-45208, or another comparable military specification or standard, you don't need to send us a copy of the standard: just identify which standard you intend to use).
  - (3) If you provide a description of your quality system, make sure that your description covers how your system:
    - --achieves defect prevention, and
    - --provides process control, and
    - --ensures adequate quality controls throughout all areas of performance.

If some of the features of your system are described in other forms (brochures, for example, or articles), you may attach a copy of such

# Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052 MOD/AMD

Page 22 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

**CONTINUATION SHEET** 

items to your response to this solicitation. If your system is described in a textbook or publication that is available from a commercial or academic distributor, include a reference to the publication by author, title, copyright date, and publisher in your system description. You need not physically attach a copy of a textbook to your offer.

- (c) If you already described your quality system as an attachment to another TACOM solicitation within the previous 90 days, you can either send us another copy, or simply identify the number of the previous solicitation.
- (d) If you do not provide us a description of your quality system, or if the description you send does not show all of the required features as stated in paragraph (b) above, your offer may be ineligible for award.
- (e) As the contractor, you shall implement and maintain a quality system that ensures the functional and physical conformity of all products or services you furnish under this contract. Your quality system shall achieve (i) defect prevention and (ii) process control, providing adequate quality controls throughout all areas of performance.
- (f) Your quality system may be based on (i) international quality standards such as the ISO 9000 series, or (ii) military, or (iii) commercial, or (iv) national quality standards. You represent that your performance under this contract will be in accordance with your quality system, which is in compliance with:

[	]	ISO 9001
[	]	ISO 9002
[	]	QS 9000
[	]	ANSI/ASQ Q9001
[	]	ANSI/ASQ Q9001
]	]	Other, specifically

(Note: if you check the <u>other</u> block because you intend to use an in-house quality system, or one based on a commercial, national, or international system not identified above, then in addition to identifying your proposed system in the space above, to the right of the word <u>other</u>, you must attach a description of this system to your offer in response to the solicitation, so that we can assess its suitability. If you receive an award, your proposed system will be required.)

- (g) Certification of compliance or registration of the quality system you identify above, by an independent standards organization or auditor, does not need to be furnished to us under this contract. However, you may attach a copy of such certification with your offer in response to the solicitation, as proof of system compliance.
- (h) At any point during performance, we have the right to review your quality system to assess its effectiveness in meeting requirements.

[End of Clause]

35 52.246-4026 LOCAL ADDRESS FOR DD FORM 250 (TACOM)

JAN/2002

- (a) The contractor must provide a copy of each Material Inspection and Receiving Report (DD 250) pertaining to this contract, to the addresses given below, using either of the following methods:
- (1) Our first preference is for you to use electronic mail (e-mail), using the following e-mail address: DD250@tacom.armv.mil
- (2) Our second preference is for you to use data facsimile (datafax) transmission, using this fax number: (586) 574-5527 and use "DD250 mailbox" in the "to:" block of your fax cover or header sheet.

In either method, do not mix DD250s from more than one contract in a single transmmission. That is, you may submit multiple DD250s in a single transmission, but they must all be against the same contract.

- (b) These copies meet the requirements for the Purchasing Office copy and the Army Inventory Control Manager copy listed in tables 1 and 2 of DFARS Appendix F.
  - (c) The DD250 form may be found, in three different formats, on the World Wide Web at http://web1.whs.osd.mil/icdhome/DD-0999.htm

[End of Clause]

## Reference No. of Document Being Continued

PIIN/SIIN W56HZV-04-P-1052

MOD/AMD

Page 23 of 24

Name of Offeror or Contractor: HUPP INDUSTRIES

ALL NON-MANUFACTURED WOOD USED IN PACKAGING SHALL BE HEAT TREATED TO A CORE TEMPERATURE OF 56 DEGREES CELSIUS FOR A MINIMUM OF 30 MINUTES. THE BOX/PALLET MANUFACTURER AND THE MANUFACTURER OF WOOD USED AS INNER PACKAGING SHALL BE AFFILIATED WITH AN INSPECTION AGENCY ACCREDITED BY THE BOARD OF REVIEW OF THE AMERICAN LUMBER STANDARD COMMITTEE. THE BOX/PALLET MANUFACTURER AND THE MANUFACTURER OF WOOD USED AS INNER PACKAGING SHALL ENSURE TRACEBILITY TO THE ORIGINAL SOURCE OF HEAT TREATMENT. EACH BOX/PALLET SHALL BE MARKED TO SHOW THE CONFORMANCE TO THE INTERNATIONAL PLANT PROTECTION CONVENTION STANDARD. BOXES/PALLETS AND ANY WOOD USED AS INNER PACKAGING MADE OF NON-MANUFACTURED WOOD SHALL BE HEAT TREATED. THE QUALITY MARK SHALL BE PLACED ON BOTH ENDS OF THE OUTER PACKAGING, BETWEEN THE END CLEATS OR END BATTENS; ON TWO SIDES OF THE PALLET.

[End of Clause]

37 52.247-4458 (TACOM)

GUARANTEED SHIPPING CHARACTERISTICS--F.O.B. DESTINATION

SEP/2000

- (a) The offeror is required to complete subparagraph (b)(1), (2), and (3), of this clause, for each part or component, including all of its packaging. This information will be used by the Government to perform logistics management functions such as providing item sustainment, planning (e.g. estimating storage costs), and redistribution. You are not liable if you give us wrong information, however since the DOD uses this data in-house in existing data bases and because this information may be used in contingency planning it, we request that the information provided be as accurate as possible.
- (b) Definitions of terms commonly used in the packaging and distribution environments are defined in ASTM D996 and should be consulted if any term used herein is in question.
  - (1) Unit Package:
- (i) Specify the type of UNIT PACKAGE for each single unit of issue: A container in direct contact with and enclosing the product along with any required protective materials(s)(e.g. item is wrapped in neutral paper, polyethylene foam cushion wrapped, sealed in a waterproof bag, and placed in a fiberboard box).
  - (ii) Unit Package Exterior Size/Weight of Unit Package with contents:

Length\_8"\_\_ x Width\_5.25"\_ x Depth \_3.5"\_(expressed in inches)/Weight expressed in \_4.0\_ pounds

- (2) Shipping Container:
  - (i) Exterior Size of SHIPPING CONTAINER AND CONTENTS THEREIN:

Length, 32"\_ x Width, 25.5"\_\_\_\_ x Height,\_\_17.25" (expressed in feet and inches)

- (ii) Number of unit packages per shipping container 84 each
- (iii) Gross weight of Shipping container and contents \_336\_ Lbs.
- (3) Unitized Loads:
  - (i) Is the Load palletized, skidded, or some other platform device used as a base for handling and transporting as a single entity. Yes [ X ] No [ ]; describe: \_\_\_\_\_\_.
  - (ii) Number of Shipping containers per pallet/skid 3 each.
  - (iii) Weight of empty pallet, skid, platform, dolly, other device used as a base for handling and transporting materials \_28\_ Lbs
  - (iv) Size of Unit Load(pallet/skid including shipping container(s)assembled for handling and transportation as a single entity:

Length,  $_4$ '\_ x Width,  $_4$ ' x Height, $_3$ 8.5" (expressed in feet and inches)

(v) Gross Weight of Unit Load 361 Lbs;

[End of Clause]

CONTIN	NUATION SHEET	Reference No. of Document Being Continued		Page 24 of 24		
CONTI	NUATION SHEET	PIIN/SIIN W56HZV-04-P-1052	MOD/AMD			
Name of Offeror or Contractor: HUPP INDUSTRIES						
LIST OF ATTACHMENT	rs					
List of			Nu	mber		
Addenda		Title	Dateof	Pages Transmitted By		
Exhibit A	TDP ON THE WEB					